



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 211-001
Product name **Adhesive Activator**
Effective date 18-Dec-2009
Company information Sprayway, Inc.
1005 Westgate
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 04
Supersedes date 13-Nov-2007

2. Hazards Identification

Emergency overview EXTREMELY FLAMMABLE LIQUID AND VAPOR. Will be easily ignited by heat, spark or flames.
Harmful in contact with eyes. Prolonged exposure may cause chronic effects.
CONTENTS UNDER PRESSURE. Aerosol.

Potential health effects

Routes of exposure Eye contact.

Eyes Contact may irritate or burn eyes. Eye contact may result in corneal injury.

Skin Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effects Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage.

Signs and symptoms Discomfort in the chest. Corneal damage. Narcosis. Conjunctivitis. Defatting of the skin. Irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
n-Butane	106-97-8	40 - 50
Acetone	67-64-1	30 - 40
Propane	74-98-6	15 - 20
Non-hazardous and other components below reportable levels		1 - 2.5

4. First Aid Measures

First aid procedures

Eye contact Remove contact lenses, if present and easy to do. Get medical attention immediately.

Skin contact Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.

Inhalation Move to fresh air. If symptoms persist, get medical attention.

Ingestion If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. In the unlikely event of swallowing contact a physician or poison control center.

5. Fire Fighting Measures

Flammable properties	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media	
Suitable extinguishing media	Alcohol foam. Dry chemical. Carbon dioxide (CO ₂). Do not use water jet.
Protection of firefighters	
Protective equipment and precautions for firefighters	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.
Methods for cleaning up	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.
Storage	Level 3 Aerosol. Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
n-Butane	106-97-8	1000 ppm	Not established	Not established
Acetone	67-64-1	500 ppm	750 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Acetone	67-64-1	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection	Wear chemical goggles.
Skin protection	Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	44.6 °F (7.2 °C) estimated
Color	Light brown.
Flammability (HOC)	37.12 kJ/g estimated
Flash back	Yes
Flash point	-156 °F (-104.4 °C) Propellant
Form	Aerosol.
Odor	aromatic amine-like
pH	Not applicable
Physical state	Gas.
Pressure	55 - 75 psig @ 70F
Solubility	Partially
Specific gravity	0.6327 estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	May include oxides of carbon.

11. Toxicological Information

Acute effects Acute LD50: 52214 mg/kg estimated, Rat, Dermal

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Acetone	67-64-1	Oral LD50 Rat 5800 mg/kg
n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h

Sensitization Not expected to be hazardous by OSHA criteria.

Teratogenicity Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity LC50 29.93 mg/L estimated, Fish, 96.00 Hours,
EC50 31911 mg/L estimated, Daphnia, 48.00 Hours,
Components of this product have been identified as having potential environmental concerns.

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F
D018: Waste Benzene

Disposal instructions Contents under pressure. Dispose of this material and its container at hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG**Basic shipping requirements:**

Proper shipping name AEROSOLS
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Labels required NONE

**IATA****Basic shipping requirements:**

Proper shipping name Aerosols, flammable
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Labels required 2.1



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Acetone: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

U.S. - Pennsylvania - RTK (Right to Know) List

Chemical	Inventory Number	Inventory Status
Acetone	67-64-1	Environmental hazard
n-Butane	106-97-8	Present
Propane	74-98-6	Present

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1*
Flammability: 4
Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MSDS sections updated

This document has undergone significant changes and should be reviewed in its entirety.

Prepared by

Regulatory Compliance