

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

957-004 **Product number**

Product name Instant Screen Opener

Effective date 27-Jul-2010 Sprayway, Inc. **Company information** 484 Vista Ave.

Addison, IL 60101 United States

General Assistance 1-630-628-3000 Company phone

800-424-9300 **Emergency telephone US Emergency telephone outside US** 703-527-3887

07 Version #

28-Dec-2009 Supersedes date

2. Hazards Identification

FLAMMABLE Emergency overview

CONTENTS UNDER PRESSURE. Aerosol. Will be easily ignited by heat, spark or

Harmful in contact with eyes. Irritating to skin. Irritating to respiratory system. Prolonged

exposure may cause chronic effects.

Potential health effects

Routes of exposure Inhalation. Ingestion. Skin contact. Eye contact.

Contact may irritate or burn eyes. Eye contact may result in corneal injury. **Eyes**

Skin Irritating to skin. Prolonged or repeated contact can result in defatting and drying of the

skin which may result in skin irritation and dermatitis (rash).

Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Inhalation

Irritating to respiratory system. Prolonged inhalation may be harmful.

Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Ingestion

Components of the product may be absorbed into the body by ingestion.

Kidney. Blood. Central nervous system. Liver. Lungs. **Target organs**

Chronic effects Unconsciousness. Conjunctiva. Liver injury may occur. Kidney injury may occur. May

cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage. Prolonged skin contact may defat the skin and produce dermatitis.

Discomfort in the chest. Corneal damage. Narcosis. Cyanosis. Liver enlargement. Signs and symptoms

Jaundice. Conjunctivitis. Defatting of the skin. Irritation.

3. Composition / Information on Ingredients

| Components | CAS# | Percent |
|--|-----------|---------|
| n-Butane | 106-97-8 | 20 - 30 |
| Cyclohexanone | 108-94-1 | 15 - 20 |
| 1,2,4-Trimethyl Benzene | 95-63-6 | 15 - 20 |
| Propane | 74-98-6 | 8 - 10 |
| Xylene | 1330-20-7 | 1 - 3 |
| Non-hazardous and other components below reportable levels | | |

4. First Aid Measures

First aid procedures

Eve contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Remove and isolate contaminated clothing and shoes. Wash off with warm water and Skin contact

soap. Get medical attention if irritation develops or persists.

Product name: Instant Screen Opener Product #: 957-Instant Screen Opener

MSDS US

Inhalation

Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention immediately.

Ingestion

If material is ingested, immediately contact a poison control center. Have victim rinse mouth thoroughly with water. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

5. Fire Fighting Measures

Flammable properties

Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media

Protection of firefighters

ing from

Specific hazards arising from the chemical

Protective equipment and precautions for firefighters

Foam. Dry chemical. Carbon dioxide (CO2). Do not use water jet.

Fire may produce irritating, corrosive and/or toxic gases.

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up

Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not smoke while using or until sprayed surface is thoroughly dry. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.

Storage

Level 3 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Level 3 Aerosol. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

| Components | CAS# | TWA | STEL | Ceiling |
|-------------------------|-----------|----------|-----------------|-----------------|
| n-Butane | 106-97-8 | 1000 ppm | Not established | Not established |
| Cyclohexanone | 108-94-1 | 20 ppm | 50 ppm | Not established |
| 1,2,4-Trimethyl Benzene | 95-63-6 | 25 ppm | Not established | Not established |
| Propane | 74-98-6 | 1000 ppm | Not established | Not established |
| Xylene | 1330-20-7 | 100 ppm | 150 ppm | Not established |

Product name: Instant Screen Opener Product #: 957 Instant Screen Opener

OSHA

| Components | CAS# | TWA | STEL | Ceiling |
|---------------|-----------|----------|-----------------|-----------------|
| Cyclohexanone | 108-94-1 | 50 ppm | Not established | Not established |
| Propane | 74-98-6 | 1000 ppm | Not established | Not established |
| Xylene | 1330-20-7 | 100 ppm | Not established | Not established |

Personal protective equipment

Eye / face protection Wear chemical goggles.

Skin protection Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant

clothing.

Respiratory protection Wear positive pressure self-contained breathing apparatus (SCBA). If permissible levels

are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied

respirator.

9. Physical & Chemical Properties

Appearance Not available

Boiling point 186.8 °F (86.1 °C) estimated

Color Colorless.

Flammability (HOC) 43.1279 kJ/g estimated

Flash back Yes

Flash point -156 °F (-104.4 °C) Propellant

Form Aerosol.

Odor Solvent.

pH Not applicable

Physical state Liquid.

Pressure 50 - 65 psig @ 70F

Solubility None

Specific gravity 0.7456 estimated

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition.

Conditions to avoid Heat, flames and sparks.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological Information

Acute effects Acute LD50: 2473 mg/kg estimated, Rat, Dermal

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

1,2,4-Trimethyl Benzene 95-63-6 Inhalation LC50 Rat 18 g/m3 4 h; Oral LD50 Rat 3400 mg/kg; Dermal LD50 Rabbit

>3160 mg/kg

Cyclohexanone 108-94-1 Inhalation LC50 Rat 10.7 mg/L 4 h; Inhalation LC50 Rat 8000 ppm 4 h; Oral LD50

Rat 800 mg/kg; Dermal LD50 Rabbit 948 mg/kg

n-Butane 106-97-8 Inhalation LC50 Rat 658 mg/L 4 h Propane 74-98-6 Inhalation LC50 Rat 658 mg/L 4 h

Xylene 1330-20-7 Inhalation LC50 Rat 5000 ppm 4 h; Inhalation LC50 Rat 47635 mg/L 4 h; Oral LD50

Rat 4300 mg/kg; Dermal LD50 Rabbit >1700 mg/kg

Sensitization Not expected to be hazardous by OSHA criteria.

Reproductive effects Components in this product have been shown to cause birth defects and reproductive

disorders in laboratory animals.

Teratogenicity Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity Components of this product are hazardous to aquatic life.

LC50 17.16 mg/L, Fish, 96.00 Hours, EC50 10.84 mg/L, Daphnia, 48.00 Hours, IC50 392 mg/L, Algae, 72.00 Hours,

Product name: Instant Screen Opener Product #: 957 Instant Screen Opener

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

Disposal instructionsContents under pressure. Do not puncture, incinerate or crush. Dispose of this material

and its container at hazardous or special waste collection point. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306
Packaging non bulk 156, 306
Packaging bulk None

IMDG

Basic shipping requirements:

Proper shipping name AEROSOLS

Hazard class 2.1 UN number 1950

Additional information:

Packaging exceptionsLTD QTYItem5FLabels requiredNoneTransport Category2

IATA

Basic shipping requirements:

Proper shipping name Aerosols, flammable

Hazard class 2.1 UN number 1950

Additional information:

Packaging exceptions LTD QTY
Labels required 2.1





15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

1,2,4-Trimethyl Benzene 95-63-6 1.0 % de minimis concentration Xylene 95-63-6 1.0 % de minimis concentration

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous Yes

chemical

CERCLA (Superfund) reportable quantity

Cyclohexanone: 5000.0000

Xylene: 100.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely No.

hazardous substance

Section 311 hazardous chemical Yes

Product name: Instant Screen Opener MSDS US

Hazard categories (311/312) Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Inventory status

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of New and Existing Chemicals (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

1,2,4-Trimethyl Benzene95-63-6Environmental hazardCyclohexanone108-94-1Environmental hazard

n-Butane 106-97-8 Present Propane 74-98-6 Present

Xylene 1330-20-7 Environmental hazard

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 1*

Flammability: 4 Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

in the text.

MSDS sections updated Product and Company Identification: Product Review

Toxicological Information: Teratogenicity

Transport Information: Product Shipping Name/Packing Group

Regulatory Information: United States

Prepared by Regulatory Compliance